

维控 130 系列伺服电机参数见下表

类别	伺服电机型号	电源	法兰	额定功率 (kW)	额定扭矩 (N.m)	额定转速 (rpm)	额定电流 (A)	最大扭矩 (N.m)
WE 系列	WE130M-10010S○☆	220V 供电	130	1	10	1000	4.5	20
	WE130M-13025S○☆			1.3	5	2500	5	15
	WE130M-15025S○☆			1.5	6	2500	6	18
	WE130M-15015S○☆			1.5	10	1500	6	25
	WE130M-20025S○☆			2	7.7	2500	7.5	22
	WE130M-23015S○☆			2.3	15	1500	9.5	30
	WE130M-26025S○☆			2.6	10	2500	10	25
	WE130M-38025S○☆			3.8	15	2500	13.5	30
	WE130M-20025T○☆	380V 供电		2	7.7	2500	6	18
	WE130M-26025T○☆			2.6	10	2500	6	25
	WE130M-38025T○☆			3.8	15	2500	7.5	22
	WE130M-42020T○☆			4.2	20	2000	8.5	60
	WE130M-53030T○☆			5.3	17	3000	9.5	30
○: A1-17bit 单圈磁编; C1-17bit 多圈磁编; D2-23bit 多圈光编。 ☆: F-油封; G-油封带抱闸。								
注 1: 以上电机选型参数仅供参考 注 2: 配置 2500 线增量式光编的电机型号, 请联系维控业务员。								