

Model	KW	HP	Rated input current(A)	Rated output current(A)	Input Voltage	General type / Fan type	Integrated with brake function
VB-4T075G/093P	75 / 90	100 / 125	157 / 180	150 / 170	380~440V / Three phase	General type / Fan type	N/A
VB-4T093G/110P	90 / 110	125 / 150	180 / 214	170 / 210	380~440V / Three phase	General type / Fan type	N/A
VB-4T110G/132P	110 / 132	150 / 180	214 / 256	210 / 253	380~440V / Three phase	General type / Fan type	N/A

Specification

Control characteristic	Control mode	V/F Control; Sensorless Vector Control (SVC); Torque Control
	Starting torque	G Type: 0.5Hz/150 % (SVC); P Type: 0.5Hz/100%
	Speed adjustment range	1:100 (SVC)
	Speed holding precision	± 0.5 % (SVC)
Overload capability	G Type: 150 % rated current for 60s; 180 % rated current for 1s P Type: 120 % rated current for 60s; 150 % rated current for 1s	
	Input / Output	
Input / Output	Input voltage	380V/415V/440V; fluctuation range: 380V(-15%)~440V(+10%)
	Input frequency	50/60Hz, fluctuation range: ±5%
	Output voltage	0-rated input voltage
	Output frequency	SVC: 0~320Hz, V/F: 0~1000Hz
	Analog input	2 channels
	Digital input	6 channels
	Input / Output terminals	Analog output
Digital output		1 channel
Relay output		2 channels
RS485 communication terminal		1 channel
Power supply		2 channels (1 channel 10V, 1 channel 24V)
Application environment	Attitude	Lower than 1000m, service is derated capability above 1000m, derate 1% capacity every 100m increased in height.
	Environment temperature	-10°C ~ + 40°C (service is derated capability for 40°C ~ 50°C)
	Humidity	<95%RH, no water condensation
	Vibration	< 5.9m/s ² (0.6g)
	Storage temperature	-40°C~+ 60°C
Enclosure	Shell Material	Metal
	Overall Size (mm)	580.00H*358.00W*328.00D
	Weight (Kg)	39
	Package dimensions (mm)	690.00H*498.00W*405.00D

