

Model	KW	HP	Rated input current(A)	Rated output current(A)	Input Voltage	General type / Fan type	Integrated with brake function
VB-4T315G/4T355P	315 / 355	430 / 480	590 / 665	585 / 650	380~440V / Three phase	General type / Fan type	N/A
VB-4T355G/4T400P	355 / 400	480 / 545	665 / 785	650 / 725	380~440V / Three phase	General type / Fan type	N/A
VB-4T400G	400	545	785	725	380~440V / Three phase	General type	N/A

Specification

Control characteristic	Control mode	V/F Control; Sensorless Vector Control (SVC); Torque Control
Starting torque		G Type: 0.5Hz/150 % (SVC); P Type: 0.5Hz/100%
Speed adjustment range		1:100 (SVC)
Speed holding precision		± 0.5 % (SVC)
Overload capability		G Type: 150 % rated current for 60s; 180 % rated current for 1s P Type: 120 % rated current for 60s; 150 % rated current for 1s
Input / Output	Input voltage	380V/415V/440V; fluctuation range: 380V(-15%)~440V(+10%)
	Input frequency	50/60Hz, fluctuation range: ±5%
	Output voltage	0-rated input voltage
	Output frequency	SVC: 0~320Hz, V/F: 0~1000Hz
	Analog input	2 channels
	Digital input	6 channels
Input / Output terminals	Analog output	2 channels
	Digital output	1 channel
	Relay output	2 channels
	RS485 communication terminal	1 channel
Application environment	Power supply	2 channels (1 channel 10V, 1 channel 24V)
	Attitude	Lower than 1000m, service is derated capability above 1000m, derate 1% capacity every 100m increased in height.
	Environment temperature	-10°C ~ + 40°C (service is derated capability for 40°C ~ 50°C)
	Humidity	<95%RH, no water condensation
	Vibration	< 5.9m/s ² (0.6g)
	Storage temperature	-40°C~+ 60°C
Enclosure	Shell Material	Metal
	Overall Size (mm)	1696.00H*800.00W*408.00D
	Weight (Kg)	246
	Package dimensions (mm)	1800.00H*945.00W*620.00D

