

Model	COM	Ethernet	Monitoring	Alarm	Data Record	Validity	WVPN Pass-through	Script
V-BOX E-00	2 in 1	1	200	50	20	60 days /1 millions	N/A	N/A
V-BOX E-4G	2 in 1	1	250	100	50	90 days /1 millions	N/A	YES

SPECIFICATIONS

Items	V-BOX E-00	V-BOX E-4G
OS		Linux
CPU	Quadcore High Performance CPU	
Flash	128MB	
RAM	DDRIII 64MB	
SD Card	N/A	
USB	OTG USB / Device USB	
Serial Port	COM1: RS232, RS422 / RS485 (2 in 1)	
Ethernet Port	1 Ethernet port	
WIFI Modules	N/A	
4G Modules	N/A	4G
Power Supply	24VDC (12~28VDC)	
Power Consumption	<10W	
Enclosure	Metal shell	
Dimension(W*H*D)	101.0mm*73.2mm*26.8mm	
Mounting Size	110.0mm*15.6mm	
Weight (KG)	0.26	
Vibration Resistance	IEC61131-2 Standard	
Storage Temperature	-20°C~70°C	
Working Temperature	-10°C~60°C	
Relative Humidity	10~85% RH (Non-condensing)	
CE Certification	CE marked	
FCC Certification	FCC Class A	
Http Interface	Yes	
Remote Update	Yes	
Configuration Backup	Yes	
Off-line Transmission	Yes	
GPS	N/A	LBS



E-4G MODEL FREQUENCY CODE

LTE FDD	LTE TDD	WCDMA	GSM
B1/B3/B5/B8	B34/B38/B39/B40/B41	B1/B5/B8	900/1800MHz

Remark: Please contact us for confirmation about 4G Compatibility before purchase.

